



SOKYMAT

GLASS TAG Hitag S - 2.12 x 8 mm

Chip type:	Hitag S – 2048 bits R/W		* Test conditions and remarks
Physical:	Diameter:	2.12 mm ± 0.1 mm	
	Length:	8.0 mm ± 1 mm	
	Material:	Glass	
	Color:	Transparent	
Electrical:	Operating frequency:	140 kHz ± 10 kHz	* At room temperature
Chemical:	Water immersion IP68		* 20°C, 24h, 1m
	Aqueous solution of salts		* 20°C, 100h
	Alcohol, oil, HLC (10%)		* 20°C, 100h
	Ammoniac		* 20°C, 100h
Mechanical:	Vibration	IEC 68-2-6	* 6g, 14...200Hz, 3 axis, 8h/axis
	Schock	IEC 68-2-29	* 30g, 18ms, 3 axis, 1084 times/axis
Thermal:	Storage:	-40°C to + 90°C	* 1 x 1000h
	Operating	-40°C to + 85°C	
Part number:	624202		

© HID reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. HID declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

CLF 3.3.3.91 - V1 - DefKey: 311930 - 06.05.2008 - Page: 1 of 1

HID Global GmbH, Am Klingenweg 6A, 65396 Walluf, Germany Tel: +49 6123 791 0 Fax: -110 email: info-emea@hidglobal.com web: www.aaitg.com & www.hidglobal.com

An ASSA ABLOY Group brand