


### ACG HF Dual ISO OEM Module RDHO-0401N0-03

The ACG HF Dual ISO OEM Module is a contact less proximity read/write device that, with its interoperability capability, supports various ISO14443A and ISO14443B RFID-devices, including the whole MIFARE® family. The module needs an external application specific antenna to operate. By using the serial interface the device can be connected to a controller or any host system easily. An integrated SAM Interface enables a state of the art security level. This RFID read/write unit is optimized for maximum data throughput rates on both, the air interface as well as the serial interface. The built in boot-loader enables firmware field upgrades via the serial interface.



### Typical Applications

- e-Payment
- e-Toll Road Pricing
- e-Ticketing for Events & Public Transport
- e-Passport
- Access Control
- PC Access
- Authentication
- Printer / Mobile Devices / Production Equipment

### Technical Data

Part Number	RDHO-0401N0-03		
RF Transmit Frequency	13.56MHz		
Supported Standards	ISO14443A, ISO14443B		
Supported Tag-ICs	MIFARE® Standard MIFARE® 4k MIFARE® Pro MIFARE® Ultralight MIFARE® DESFIRE MIFARE® SmartMX	SLE 55Rxx SLE 66CL160S SLE 66CLX320P SR176 SRIX4K	ISO14443A Tags ISO14443B Tags Jewel Tag (IRT0302B11 KSW DIY Eng. Sample) Sharp B ASK GTML2ISO <b>TOSMART P064</b>
Host Communication	Point-to-Point		
Communications Interface	CMOS-TTL		
Communications Protocol	Specific ASCII or Binary Protocol		
Communications Parameter	9600 Bit/s to 460 kBit/s, 8,N,1		
Firmware Boot-Loader	Supported Via Serial Interface		
S/W Driver	DLL and API available (VC++), PC/SC Driver for MS Windows 2000/XP		
Power Supply	5VDC regulated		
Current Consumption	90 – 200 mA depending on antenna < 10µA at power down mode		
Reading distance	up to 95 mm, depending on tag and antenna		
RF Transmission Speed	up to 848 kBit/s		
Antenna	External		
Input/Output Connector	Read indicator LED, 1 I/O Port, SAM Interface		
Size	(LxWxH) 25.5x30.0x4.8mm ± (L/W) 0.5 (H) 1.0 / 1.00x1.18x0.19Inch ± (L/W) 0.02 (H) 0.04		
Weight	5g ± 5% / 0.01 lb± 5%		
Operating Temperature	-20°C to +80°C / - 4F to + 176F		
Storage Temperature	-40°C to +85°C / - 40F to + 185F		
Firmware Version	2.2		

For more information, please contact the sales office nearest you or visit our website: [www.acg.de/RFID](http://www.acg.de/RFID)

ACG Identification Technologies GmbH reserves the right to change its services and products at any time without prior notice. ACG provides customer assistance in various technical areas, but does not have full access to data concerning the uses and applications of customer products. Therefore, ACG assumes no responsibility for customer product designs or for infringement of patents and/or the rights of third parties, which may result from assistance provided by ACG.