



Zebra® R4Mplus™

RFID Printer/Encoder
for EPC Class 1 Tags

RFID. Bar Coding. We've Got You Covered.

The R4Mplus builds on Zebra's rich heritage as a leader in on-demand bar code compliance labeling solutions and as the pioneer of the first radio frequency identification (RFID) smart label printer/encoder on the market. The R4Mplus helps you to comply with the RFID supply chain requirements of major retailers and government agencies as it also enhances efficiencies within your own company. Plus, the R4Mplus is designed to support Electronic Product Code™ (EPC) RFID standards as they develop—making it an ideal solution as you move forward with your RFID initiatives.

Flexible and Reliable

Able to support ultra-high-frequency (UHF) Class 1 transponders from Alien Technology, the R4Mplus offers unique flexibility by providing both "read and write" and "read only" options. UHF transponders are perfect for tagging pallets, cartons, and cases throughout the supply chain because their long read ranges allow for unattended batch reading. Count on the R4Mplus with die-cast metal construction for dependable performance in your distribution center or warehouse environment.

With support for EPC UHF Class 1 tags, the R4Mplus printer/encoders are perfect for pilots, field tests, and demonstration projects for:

- Inventory management
- Asset tracking
- Distribution
- Shipping/Receiving
- Supply chain management



R4Mplus



Confidently advance your EPC RFID compliance and business improvement initiatives with the UHF R4Mplus for Class 1 tags.

STANDARD FEATURES

Integrated UHF RFID reader/encoder for EPC Class 1 (Alien) tags
Print methods: Thermal transfer or direct thermal
Construction: Die-cast aluminum base, frame and printhead mechanism
Metal media cover with large clear window
Multi-level Element Energy Equalizer™ (E³) for superior print quality
Auto-calibration
Adjustable transmissive sensor
Real-time clock
Auto-ranging (110 V–220 V) power supply
Color-coded operator cues
Back-lit LCD control panel

PRINTER SPECIFICATIONS

Resolution

203 dpi/8 dots per mm

Memory

Standard: 4 MB Flash, 2 MB user available, 8 MB DRAM

Print Width

Width: 4.09"/104 mm

Print Length

Length: 165"/4,202 mm

Print Speed

10"/254 mm per second

Media Sensors

Transmissive

Specifications at a Glance*

MEDIA CHARACTERISTICS

Smart Labels

Maximum label and liner length

39" /991 mm

Maximum label and liner width

4.50" /114 mm Tear/Cutter; 4.25" /108 mm Peel/Rewind

Maximum roll diameter

8" /203 mm O.D. on a 3" /76 mm I.D. core

Core diameter

3" /76 mm

Media thickness

.0023" /0.058 mm to .01" /0.25 mm

Media types

Continuous or fanfold, die-cut, notched, tag stock, perforated

For optimum print quality and performance, use Genuine Zebra Supplies.

Supported Transponder Types

EPC UHF Class 1 (draft specification)
Alien Technology (64-bit memory)

RIBBON CHARACTERISTICS

Outside diameter

3.2" /81.3 mm

Standard length

1476' /450 m

Ratio

3:1

Width

2.0" /51 mm to 4.33" /110 mm

Ribbon setup

Ribbon wound ink side out

Core I.D.

1" /25.4 mm

OPERATING CHARACTERISTICS

Environmental

Operating temperature

32° F/0° C to 104° F/40° C (Direct Thermal);
40° F/5° C to 104° F/40° C (Thermal Transfer)

Storage temperature -40° F/-40° C to 140° F/60° C

Operating humidity 20-85% non-condensing

Storage humidity 5-85% non-condensing

Electrical

Universal auto-ranging (PFC-compliant) power supply 90-265 VAC; 48-62 Hz; 5A fused

Agency approvals

cULus, FCC-B

PHYSICAL CHARACTERISTICS

Width: 10.93" /278 mm

Height: 13.32" /338 mm

Depth: 18.69" /475 mm

Weight: 32.4 lb/15 kg

Shipping weight: 49 lb/22 kg

RELATED PRODUCTS

Options

Optional Memory:

-Up to 32 MB additional linear Flash via PCMCIA

-Up to 256 MB additional ATA format via PCMCIA or CompactFlash cards

Memory socket board option

ZEBRALINK™ SOLUTIONS

Software

ZebraDesigner™ Pro

Zebra Universal Driver

Networking

ZebraNet™ Bridge Enterprise

ZebraNet® PrintServer II (internal or external)

Firmware

ZPL II®—Universal language for Zebra printers.

Simplifies label formatting and enables format compatibility with other Zebra printers.

COMMUNICATION AND INTERFACE CAPABILITIES

RS-232 serial port

High-speed, IEEE1284, bi-directional parallel interface

RS-422/485 serial port adapter

BAR CODES/SYMBOLOGIES

Linear Bar Codes

Code 11, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Case C Codes, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2 or 5 digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar, Planet Code, RSS

2-Dimensional

Codablock, PDF417, Code 49, Data Matrix, MaxiCode, QR Code, Micro PDF417, TLC 39, RSS

FONTS AND GRAPHICS

Fonts

7 bitmapped, 1 smooth scalable (CG Triumvirate™ Bold Condensed)

Sets: International character sets supporting the following code pages: IBM® Code Page 850

International character set

Contains UFST® from Agfa Monotype Corporation

Optional European and Asian font sets

Graphic Features

Supports user-defined fonts and graphics—including custom logos

ZPL II drawing commands—including boxes and lines

Not all products are available worldwide due to country-specific government regulations. Contact your Zebra representative for product availability.

* Specifications subject to change without notice. ©2005 ZIH Corp. ZebraLink, ZebraNet, ZebraDesigner, Element Energy Equalizer and all product names and numbers are Zebra trademarks, and Zebra, E³, ZebraNet, and ZPL II are registered trademarks of ZIH Corp. All rights reserved. Electronic Product Code is a trademark of EPCglobal Inc. CompactFlash is a registered trademark of SanDisk Corporation. IBM is a registered trademark of International Business Machines Corporation. CG Triumvirate is a trademark of Agfa Division, Miles Inc. UFST is a registered trademark of Agfa Monotype Corporation. All other trademarks are the property of their respective owners.



HEADQUARTERS Zebra Technologies International, LLC **T:** +1 847 793 2600 or +1 800 423 0442 **F:** +1 847 913 8766

ADDRESS: 333 Corporate Woods Parkway, Vernon Hills, IL 60061-3109 U.S.A. **WEB:** www.zebra.com

OTHER LOCATIONS **USA:** California, Florida, Rhode Island, Wisconsin **EUROPE:** Denmark, France, Germany, Italy, Netherlands, Spain, Sweden, United Kingdom **ASIA-PACIFIC:** Australia, China, Japan, Singapore, South Korea
LATIN AMERICA: Argentina, Brazil, Mexico **AFRICA/MIDDLE EAST:** South Africa, United Arab Emirates



An ISO 9001 registered company
GSA#: GS-35F-0268N
©2005 ZIH Corp. Printed in U.S.A.
#13544L Rev. 6 (7/05) 10M