


ACG HF Multi ISO Compact Plug & Play Module

RDHC-0202N0-01

The ACG HF Multi ISO Compact Plug & Play Module is a contact less proximity read/write device that supports various ISO14443A/B, ISO 15693, ISO 18000-3 and EPC RFID-devices, including the whole MIFARE® family. The module has a built in antenna. By using the RS232 interface the device can be connected to a PC or any other host system easily. An integrated SAM Socket enables a state of the art security level. This RFID read/write unit is optimized for maximum data throughput rates on both, the air interface as well as the serial interface. The built in boot-loader enables firmware field upgrades via the serial interface.



Typical Applications

- e-Payment
- e-Toll Road Pricing
- e-Ticketing for Events & Public Transport
- Access Control
- PC Access
- Authentication
- Logistics & Supply Chain Management
- Printer / Production Equipment

Technical Data

Part Number	RDHC-0202N0-01		
RF Transmit Frequency	13.56MHz		
Supported Standards	ISO14443A, ISO14443B, ISO 15693, ISO 18000-3, ICODE		
Supported Tag-ICs	MIFARE® Standard MIFARE® 4k MIFARE® Pro X MIFARE® Ultralight MIFARE® DESFIRE MIFARE® SmartMX I-CODE SLI (SL2 ICS 20) I-CODE EPC (SL2 ICS 10) I-CODE UID (SL2 ICS 11) I-CODE	SLE 55Rxx SRF55VxxP +S SLE 66CL160S SLE 66CLX320P SR176 SR1X4K LRI 12 LRI 64 LRI 512 EM4135 KSW Temp Sense	Tag-it™ HF-I Tag-it™ HF-I Light S Jewel Tag (IRT0302B11 KSW DIY Eng. Sample) Sharp B ASK GTML ASK GTML2ISO TOSMART P064 ISO14443A Tags ISO14443B Tags ISO15693 Tags
Host Communication	Point-to-Point		
Communications Interface	RS232		
Communications Protocol	Specific ASCII or Binary Protocol		
Communications Parameter	9600 Bit/s to 115 kBit/s, 8,N,1		
Firmware Boot-Loader	Supported Via Serial Interface		
S/W Driver	Virt. COM port Driver, API - DLL (VC++), PC/SC Driver for MS Win 2000/XP (for Mifare and 14443-4 only)		
Power Supply	5V DC ± 10% regulated		
Current Consumption	150 mA < 10mA at power down mode		
Reading distance	Up to 85mm, depending on tag and antenna		
RF Transmission Speed	up to 848 kBit/s		
Antenna	Integrated		
Input/Output Connector	Read indicator LED, 1 I/O Port, SAM Socket		
Size	(LxWxH) 70.0x45.0x12.1mm ± 1.0mm / 2.76x1.77x0.48 Inch ± 0.04 Inch		
Weight	17g ± 10% / 0.04 lb ± 10%		
Operating Temperature	-20°C to +80°C / -4F to +176F		
Storage Temperature	-40°C to +85°C / -40F to +185F		
Firmware Version	1.0		
Approvals	ETS 300-330, CE, FCC pending		

For more information, please contact the sales office nearest you or visit our website: www.acg.de/RFID

ACG Identification Technologies GmbH reserves the right to change its services and products at any time without prior notice. ACG provides customer assistance in various technical areas, but does not have full access to data concerning the uses and applications of customer products. Therefore, ACG assumes no responsibility for customer product designs or for infringement of patents and/or the rights of third parties, which may result from assistance provided by ACG.