

Desktop Reader/Writer – 13,56MHz

The iDTRONIC desktop reader versions allow the administration (reading and writing) of all well known 13,56MHz transponders. All desktop reader versions are equipped with an USB or RS232 interface and signal LED.

The USB version shows its advantage in a convenient connection to the PC. These models are supplied with USB cable. The RS232 versions come with serial cable and power supply.

All iDTRONIC desktop readers come with application software for Read/Write.



Applications:

- Encoding
- Programming

Product specification:

Interface:	USB or RS232
Integrated antenna:	Yes
Operating system:	Windows
Power supply:	5Vdc/60mA – Bus-self powered
Signals:	1 LED
Reading distance:	Up to 8 cm (depending on version and type of transponder)
Operating temperature:	0°C ...+50°C
Dimensions:	155 x 96 x 20mm
Material:	ABS
Colour:	grey

Desktop Reader Versions:

Desktop Readers:	Supported transponders:	Order number:
ISO15693	NXP I-Code SLI	R-DT-15693-USB (USB version) R-DT-15693-232 (RS232 version)
ISO14443A	NXP Mifare MF1S50 NXP Mifare MF1S70 NXP Mifare MF0U10 (UL)	R-DT-A-232 (RS232 version) R-DT-A-USB (USB version)