





COIN Mifare® 1K

Description	Proximity coin designed to suit most HF applications			
IC type:	Mifare® 1K MF1 IC S50			
Physical:	Diameter:	17.8 mm	± 0.3 mm	
	Thickness:	1.7 mm	± 0.3 mm	
	Color:	Black		
Electrical:	Operating Frequency:	13.56 MHz		
Storage temp:	-40°C to +70°C	(-40°F to +158°F)		ISO/IEC 10373
Operating temp:	-30°C to +70°C	(-22 ^O F to +158 ^O F)		ISO/IEC 10373
	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			150.00.0
Mechanical:	Vibration			IEC 68-2-6
	Shock			IEC 68-2-29
	Drop test 10 times 10 cycles (1.8m)			
Material:	Epoxy PT365			
Immersion:	Water IP67			ISO/IEC 60529
Options:	For full options list, please visit our website: www.aaitg.com			
Part number:	607152			

[®] HID reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. HID declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

CLF 3.3.2.80 - V1 - DefKey: 3313773 - 30.10.2008 - Page: 1 of 1