

# IronTag®

## Compact UHF RFID tags that enable tracking of metal assets in harsh environments

IronTag® UHF transponders deliver exceptional performance on metal surfaces, and they are built to withstand vibration, shock, chemical exposure and fluctuating temperatures. The transponders enable radio frequency identification (RFID) tagging of metal equipment and components that are subject to severe conditions.




Designed for tracking aircraft parts, IronTag devices tolerate the harsh conditions of vehicle and equipment manufacturing, processing and operation. They handle temperatures from -40° F (-40° C) to 428° F (220° C), are waterproof, resist high-pressure/high-temperature washing and withstand exposure to fuels, oils, salt water and ultraviolet light. They are resistant to pressure (<100 bar), vibration and steady flame for short periods. IronTag 206 units deliver the highest flame resistance rating available.

Compact and powerful, these tags offer robust performance with read ranges of up to 13 ft (4 m), and large user memory capacities up to 8192 bits.

Durable IronTag RFID tags mount to any metal surface with industrial glues or optional high-temperature stickers, making them ideal for logistics applications that track metal components through assembly, operation, maintenance and repair.

The smaller, lighter-weight IronTag 206 device features flanges on two sides and pre-drilled holes, enabling additional secure fixation options via clamps or screws. Also available in a fully flat 206F version.

Patent-pending designs meet standards for the most demanding industries, including aircraft manufacturing and fleet management. They are ideal for metallic asset tracking applications where a small form factor and durability are vital.



### KEY BENEFITS:






- Extreme durability – waterproof, and resistant to flame, chemicals, vibration, shock and temperature fluctuations
- Exceptional size-to-performance ratio – reliably read-write when mounted on metal objects from up to 13 ft (4 m)
- Advanced technology – UHF permits anti-collision capability and fast data rate communication

### TECHNOLOGY HIGHLIGHTS:

- 869 or 915 MHz
- Up to 8192 bit read-write memory, 128 bit EPC
- Reliable performance on metal surfaces
- Waterproof even under high pressure or high temperature; chemical, UV and flame resistant
- Thermal protection from -40° F (-40° C) to 428° F (220° C)
- Standards compliant

### APPLICATION AREAS:

- Asset tracking and logistics
  - Equipment
  - Fleet management
  - Machinery
  - Metal tools
- Automation and manufacturing
  - Assembly line management
  - Aircraft parts tracking
  - Industrial component tracking

	Iron Tag®				
	176		206		206F
					
<b>Base Model Number</b>	698901-010	698902-010	6D3903 (8 kbits)	6D3904 (8 kbits)	6D3905 (8 kbits)
<b>ELECTRONIC</b>					
<b>Operating Frequency</b>	865-868 MHz (ETSI)	902-928 MHz (FCC)	865-868 MHz (ETSI)	902-928 MHz (FCC)	860-960 MHz (Worldwide)
<b>Chip Type</b>	Higgs 3		Monza X		
<b>User Memory</b>	512 bit		8192 bit	8192 bit	8192 bit
<b>Memory</b>	96 bit EPC, 64 bit TID		128 bit EPC, 96 bit TID		
<b>Anti-Collision</b>	Yes				
<b>Reading Distance (2W reader ERP, free space)</b>	Up to 13.1 ft (4 m), on-metal		Up to 8.2 ft (2.5 m), on-metal		Up to 6.6 ft (2 m), on-metal
<b>PHYSICAL</b>					
<b>Dimensions</b>	2.1 x 0.9 x 0.27 in (53 x 23 x 7 mm)		1.32 x 1.22 x 0.24 in (33.7 x 31.1 x 6.1 mm)		1.22 x 1.22 x 0.24 in (31 x 31 x 6.9 mm)
<b>Mounting Method</b>	Glue, optional sticker		Clamp, glue, screw; optional sticker		
<b>Screw Fixation Hole</b>	n/a		Ø 0.13 in (3.3 mm)		
<b>Affixes To</b>	Metal surfaces				
<b>Housing Material</b>	PPA, Polyphthalamide, (ISO PA6T/6I)		PPS, Polyphenylene Sulfide		
<b>Color</b>	Black				
<b>Weight</b>	0.52 oz (14.7 g)		0.35 oz (9.9 g)		0.03 oz (13 g)
<b>CHEMICAL AND MECHANICAL</b>					
<b>Water</b>	IP68, 68° F (20° C), 3.3 ft (1 m) x 24 h; IP69K (100 bar at 80° C, 30 sek., 16 l/min)		IP67, 68° F (20° C), 3.3 ft (1 m) x 1 h		IP68, 68° F (20° C), 3.3 ft (1 m) x 24 h; IP69K (100 bar at 80° C, 30 sek., 16 l/min)
<b>Withstands Exposure To</b>	Fuel B, mineral oil, petroleum, salt mist, vegetable oil; UV (ISO 4892-2)				
<b>Environmental Test Conditions</b>	68° F (20° C), 100 h				
<b>Flame resistance</b>	UL 94 HB, food compatible		UL 94 V0		
<b>Vibration</b>	IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h]				
<b>Shock</b>	IEC 68.2.29 [40 g, 18 ms, 6 axis, 2000 times]				
<b>Impact</b>	IEC 62262-IK07		IEC 62262-IK06		
<b>Axial / Radial Force</b>	800 N / 500 N, 10 sec				
<b>THERMAL</b>					
<b>Storage</b>	-40° to +194° F (-40° to +90° C), 1000 h				
<b>Operating</b>	-40° to +185° F (-40° to +85° C)				
<b>Shock/Fatigue</b>	-40° to +194° F (-40° to +90° C), 100 x 5 min with 30 sec transition		-67° to +302° F (-55° to +150° C), 500 x 5 min with 30 sec transition		-67° to +212° F (-55° to +100° C), 200 x 5 min with 30 sec transition
<b>Peak (one time)</b>	356° F (180° C) 400 h		302° F (150° C) 1000h, 356° F (180° C) 400 h, 392° F (200° C) 24 h, 428° F (220° C) 10 h		212° F (100° C) 1000 h
<b>OTHER</b>					
<b>Standards</b>	UHF EPC Class 1 Gen 2; ISO/IEC 18000-6C; GS1 EPC TDS 1.6; DIN 40050-9		UHF EPC Class 1 Gen 2; ISO/IEC 18000-6C; GS1 EPC TDS 1.6; ATA Spec 2000; SAE AS5678; DIN 40050-9		UHF EPC Class 1 Gen 2; ISO/IEC 18000-6C; GS1 EPC TDS 1.6; DIN 40050-9
<b>Box Size</b>	250 pcs				
<b>Options</b>	High bond, high temperature adhesive (add *-001* after part number); alternate embossed logo				
<b>Warranty</b>	2 Years				

For further information, contact [tagsales@hidglobal.com](mailto:tagsales@hidglobal.com)



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769

Europe, Middle East, Africa: +44 1440 714 850

Asia Pacific: +852 3160 9800 | Latin America: +52 (55) 9171-1108

For more global phone numbers click here

© 2021 HID Global Corporation/ASSA ABLLOY AB. All rights reserved.

2021-11-11-11-idt-rfid-ii-iron-tag-ds-en PLT-02314

Part of ASSA ABLLOY