

RFID Keyfob EASY

iDTRONIC's Keyfob EASY combines the RFID technology with a complete new customizable keyfob. It is offered with offset printing of customized design or logo. The printing of a serial number or barcode is possible as well. The keyfob EASY is available with all common ICs in 125 kHz and 13.56 MHz technology.

Applications:

- Access Control
- Identification
- Time Attendance
- Health Clubs

Personalisation options:

- Offset Printing with customer design/logo (for both sides)
- Serial number thermo print
- Barcode



Product specification:

Material:	PVC
Dimensions:	30 x 45 x 1.1 mm
Surface:	Matt
Application temp. :	-20 °C to +65 °C

Available 125 kHz systems:

IC Type	Memory	Mode
EM 4100/4200	8 Bytes	Read-Only
EM 4450/4550	125 Bytes	R/W
Atmel Temic 5567	28 Bytes	R/W
NXP Hitag 1	256 Bytes	R/W
NXP Hitag 2	32 Bytes	R/W
NXP Hitag S	64/256 Bytes	R/W

Available 13.56 MHz systems:

IC Type	ISO	Memory
NXP MIFARE Ultralight®	14443A	64 Bytes
NXP MIFARE® Classic 1K EV1	14443A	1024 Bytes
NXP MIFARE® Classic 4K	14443A	4096 Bytes
NXP MIFARE® DESFire® EV1	14443A	-
NXP I-Code SLI	15693	64 Bytes
NXP I-Code SLI-S	15693	256 Bytes
LEGIC MIM256	-	256 Bytes
LEGIC MIM1024	-	1024 Bytes