

RFID Keyfob EPOXY

iDTRONIC RFID keyfobs combine the RFID technology with good looking and practical keyfob housings. They can easily be fitted to a normal key ring. They are available with all common ICs in 125 kHz as well as in 13.56 MHz.



The iDTRONIC Epoxy keyfob is among the most robust keyfobs in the market.

Applications:

- Access Control
- Identification
- Time Attendance
- Health Clubs

Personalization Option:

- Laser Engraved Number

Product specification:

Dimensions:	45 x 30 x 1.6 mm
Weight:	7 g
Material:	Glass fibre
Colour:	black
Surface:	opaque
Application temp. :	up to +130 °C

Available 125 kHz systems:

IC Type	Memory	Mode
EM 4100/4200	8 bytes	Read-Only
EM 4450/4550	125 bytes	R/W
Atmel Temic 5567	28 bytes	R/W
NXP Hitag1	256 bytes	R/W
NXP Hitag2	32 bytes	R/W
NXP HitagS	64/256 bytes	R/W

Available 13.56 MHz systems:

IC Type	ISO	Memory
NXP MIFARE Ultralight®	14443A	64 bytes
NXP MIFARE® Classic 1K EV1	14443A	1024 bytes
NXP MIFARE® Classic 4K	14443A	4096 bytes
NXP MIFARE® DESFire® EV1	14443A	-
NXP I-Code SLI	15693	64 bytes
NXP I-Code SLI-S	15693	256 bytes
LEGIC MIM256	-	256 bytes
LEGIC MIM1024	-	1024 bytes