

RFID Keyfob “SAIL”

iDTRONIC RFID keyfobs combine the RFID technology with good looking and practical keyfob housings. They can easily be fitted to a normal key ring. They are available with the most common ICs in 125kHz as well as in 13,56MHz.

The keyfob SAIL comes in an attractive semi-transparent housing which give you a view on the RFID unit inside.



Applications:

- Access Control
- Identification
- Time Attendance
- Health Clubs

Personalisation options:

- Laser Engraved number

Product specification:

Dimensions:	55 x 32 x 8mm
Weight:	7g
Material:	Polycarbonat
Colours:	grey, blue, red
Surface:	opac
Humidity resistance:	IP 67
Application temp.:	- 25°C to 65°C

Available 125kHz systems:

IC Type	Memory	Mode
EM 4100/4200	8 byte	Read Only
EM 4450/4550	125 byte	R/W
Atmel Temic 5567	28 byte	R/W
NXP Hitag1	256 byte	R/W
NXP Hitag2	32 byte	R/W
NXP HitagS	64 / 256 byte	R/W

Available 13,56MHz systems:

IC Type	ISO	Memory
NXP MIFARE Ultralight®	14443A	64 byte
NXP MIFARE® Classic 1K EV1	14443A	1024 byte
NXP MIFARE® Classic 4K	14443A	1024 byte
NXP MIFARE® DESFire® EV1	14443A	-
NXP I-Code SLI	15693	64 byte
NXP I-Code SLI-S	15693	256 byte
LEGIC MIM256	-	256 byte
LEGIC MIM1024	-	1024 byte