

Volcano Tag™

DURABLE LOW FREQUENCY RFID TAGS THAT PERFORM IN HIGH TEMPERATURE ENVIRONMENTS

- **High heat tolerance** – during storage, industrial processing, transportation and outdoor use
- **Durable housing** – withstands rigors of chemical and mechanical exposure
- **Versatile** – screw-mounts securely anywhere without compromising performance: glass, metal, plastic, or wood



Volcano Tag™ passive contactless radio frequency identification (RFID) transponders are built for reliable performance in high-heat conditions. For RFID applications where tags must perform before, amidst or following extreme heat exposure, Volcano Tag discs withstand peak temperatures up to 392° F (200° C).

Volcano Tag housings are composed of field-proven, temperature-stable polyphthalamide (PPA). This thermoplastic shell holds its shape despite high or fluctuating temperatures, protecting the electronics within. Exceptional

toughness, chemical resistance and abrasion resistance assure consistent communications with RFID readers, and reliable performance in automation and manufacturing applications.

Low frequency (LF) Volcano Tag discs perform well affixed to virtually any surface – glass, metal, plastic or wood. They offer reliable, cost-effective tagging for near-proximity reader applications, with available data storage from a 64-bit user ID up to 264-bit read-write capability.

For additional disc-tag options, the HID Global IN Tag™ and Poly Tag families also include heavy-duty tags in low frequency, high frequency and UHF configurations. For lighter-duty applications, consider HID Epoxy Disc or World Tag™ RFID tags.



TECHNOLOGY HIGHLIGHTS:

- Peak temperature up to 392° F (200° C)
- Operating frequency 125 kHz
- Up to 264 EEPROM
- Waterproof
- Mount-ready, via central screw hole

APPLICATION AREAS:

- Automation and manufacturing
 - High temperature production processes
 - Machinery



HID Global can create a custom tag solution to fit your application requirements for chip type, dimensions, programming and materials.



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769

Europe, Middle East, Africa: +44 1440 714 850

Asia Pacific: +852 3160 9800 | Latin America: +52 (55) 9171-1108

For more global phone numbers click here

© 2022 HID Global Corporation/ASSA ABLOY AB. All rights reserved.

2022-01-14-hid-rfid-il-volcano-tag-ds-en PLT-00285

Part of ASSA ABLOY

VOLCANO TAG™

	231	
Base Model Number	612170	601170
	ELECTRONIC	
Operating Frequency	125 kHz	
Chip Type	Q5	Unique
Memory	264 bit EEPROM	64 bit read-only
Anti-Collision	N/A	
Reading Distance	Dependent upon reader, environment and application	
	PHYSICAL	
Dimensions	Ø 1.02 x 0.16 in (Ø 26 x 4 mm)	
Mounting Method	Screw	
Fixation Hole Size	Ø 0.18 in (4.5 mm)	
Affixes To	Glass, metal, plastic, wood	
Housing Material	PPA	
Color	Black	
Weight	0.12 oz (3.5 g)	
	CHEMICAL AND MECHANICAL	
Water	IP68, 68° F (20° C), 3.3 ft (1 m) x 24 h	
Vibration	IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h]	
Shock	IEC 68.2.29 [40 g, 18 ms, 6 axis, 2000 times]	
	THERMAL	
Storage	-13° to +284° F (-25° to +140° C), 1000 h	
Operating	-13° to +185° F (-25° to +85° C)	
Shock/Fatigue	68° to +320° F (20° to +160° C), 100 x 5 min with 20 sec transition	
Peak	+320° F (+160° C) 1 x 100 h; 392° F (+200° C) 10 x 10 min	
	OTHER	
Box Size	800 pcs	
Warranty	2 Years	

For further information, contact tagsales@hidglobal.com

