

# World Tag™

## COST-EFFECTIVE, LOW FREQUENCY DISC-SHAPED RFID TAGS FOR INDOOR APPLICATIONS

- **Cost-effective** – low cost discs deliver excellent size to performance ratios
- **Versatile** – screw or glue mount securely to glass or plastic



HID Global World Tag™ passive contactless transponders deliver reliable, cost-effective radio frequency identification (RFID) tag performance for light-duty, indoor applications.

World Tag devices are made of durable polycarbonate, protecting the electronics within. Each tag withstands manufacturing and processing temperatures of 212° F (100° C) or higher, enabling encapsulation of World Tag transponders in a broad range of end-use housings or use as is.

Low frequency (LF) World Tag discs perform best affixed to wood, glass or plastic surfaces. They offer reliable, cost-effective tagging for near-proximity reader applications, with available data storage from a 64-bit user ID, up to 2048-bit read-write capability.

World Tag RFID tags are available in 20 mm, 30 mm and 50 mm diameters to match read range requirements, and are available with a variety of integrated chips.

For additional options, the heavy-duty HID IN Tag™, Epoxy Tag and Poly Tag families offer low frequency, high frequency and UHF configurations.



### TECHNOLOGY HIGHLIGHTS:

- Operating frequency 125 kHz
- Peak temperature up to 212 F (100° C)
- Up to 256 bit
- Polycarbonate housing
- Mount-ready, via glue or screw hole



HID can create a custom tag solution to fit your application requirements for chip type, dimensions, programming and materials.

## APPLICATION AREAS:







- Asset tracking and logistics
  - Boxes, containers
  - Furniture
  - Equipment
- OEM service and maintenance
  - Repair schedules
  - Ownership logs

## WORLD TAG

### Hitag S

		
	<b>20 mm</b>	<b>30 mm</b>
<b>Base Model Number</b>	623102	623103
	<b>ELECTRONIC</b>	
<b>Operating Frequency</b>	125 kHz	
<b>Chip Type</b>	HITAG S	
<b>Memory</b>	256 bit EEPROM	256 bit EEPROM
<b>Anti-Collision</b>	YES	
<b>Reading Distance</b>	Dependent upon reader, environment and application	
	<b>PHYSICAL</b>	
<b>Dimensions</b>	Ø 0.79 x 0.08 in (Ø 20 x 2.1 mm)	Ø 1.18 x 0.08 in (Ø 30 x 2.1 mm)
<b>Mounting Method</b>	Glue, embed	Screw
<b>Fixation Hole Size</b>		Ø 0.13 in (3.2 mm)
<b>Affixes To</b>	Glass, plastic, wood	
<b>Housing Material</b>	PC	
<b>Color</b>	Black	
<b>Weight</b>	0.03 oz (0.8 g)	0.07 oz (1.9 g)
	<b>MECHANICAL RESISTANCE</b>	
<b>Vibration</b>	IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h]	
<b>Shock</b>	IEC 68.2.29 [40 g, 18 ms, 6 axis, 2000 times]	
<b>Axial / Radial Force</b>	500 N / 300 N, 10 sec	
	<b>THERMAL</b>	
<b>Storage</b>	-40° to +194° F (-40° to +90° C), 1000 h	
<b>Operating</b>	-13° to +158° F (-25° to +70° C)	
<b>Shock/Fatigue</b>	-13° to +158° F (-25° to +70° C), 50 x 10 min with 30 sec transition	
<b>Peak</b>	212° F (100° C), 100 h	
	<b>OTHER</b>	
<b>Box Size</b>	2,000 pcs	1,000 pcs
<b>Options</b>	Custom printed logo	
<b>Warranty</b>	2 Years	

# WORLD TAG

	Q5		Titan		Unique	
						
	<b>20 mm</b>	<b>30 mm</b>	<b>30 mm</b>	<b>20 mm</b>	<b>30 mm</b>	<b>50 mm</b>
<b>Base Model Number</b>	612102	612103	602103	601102-001	601103	601104
	<b>ELECTRONIC</b>					
<b>Operating Frequency</b>	125 kHz					
<b>Chip Type</b>	Q5		Titan	Unique		
<b>Memory</b>	264 bit EEPROM		1024 bit EEPROM	64 bit read-only		
<b>Anti-Collision</b>						
<b>Reading Distance</b>	Dependent upon reader, environment and application					
	<b>PHYSICAL</b>					
<b>Dimensions</b>	Ø 0.79 x 0.08 in (Ø 20 x 2.1 mm)	Ø 1.18 x 0.08 in (Ø 30 x 2.1 mm)	Ø 1.18 x 0.08 in (Ø 30 x 2.1 mm)	Ø 0.79 x 0.08 in (Ø 20 x 2.1 mm)	Ø 1.18 x 0.08 in (Ø 30 x 2.1 mm)	Ø 1.97 x 0.08 in (Ø 50 x 2.1 mm)
<b>Mounting Method</b>	Glue, embed	Screw	Screw	Glue, embed	Screw	
<b>Fixation Hole Size</b>		Ø 0.13 in (3.2 mm)	Ø 0.13 in (3.2 mm)		Ø 0.13 in (3.2 mm)	Ø 0.17 in (4.2 mm)
<b>Affixes To</b>	Glass, plastic, wood					
<b>Housing Material</b>	PC					
<b>Color</b>	White					
<b>Weight</b>	0.03 oz (0.8 g)	0.07 ozn(1.9 g)	0.07 ozn(1.9 g)	0.03 ozn(0.8 g)	0.07 oz (1.9 g)	0.18 oz (5.2 g)
	<b>MECHANICAL RESISTANCE</b>					
<b>Vibration</b>	IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h]					
<b>Shock</b>	IEC 68.2.29 [40 g, 18 ms, 6 axis, 2000 times]]					
<b>Axial / Radial Force</b>	500 N / 300 N, 10 sec		500 N / 300 N, 10 sec	500 N / 300 N, 10 sec		500 N / 100 N, 10 sec
	<b>THERMAL</b>					
<b>Storage</b>	-40° to +194° F (-40° to +90° C), 1000 h					
<b>Operating</b>	-13 °to +158° F (-25° to +70° C)					
<b>Shock/Fatigue</b>	-13° to +158° F (-25° to +70° C), 50 x 10 min with 30 sec transition					
<b>Peak</b>	212° F (100° C), 100 h					
	<b>OTHER</b>					
<b>Box Size</b>	2000 pcs	1000 pcs	1000 pcs	2000 pcs	1000 pcs	250 pcs
<b>Options</b>	Custom printed logo					
<b>Warranty</b>	2 Years					

For further information, contact [tagsales@hidglobal.com](mailto:tagsales@hidglobal.com)



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769  
 Europe, Middle East, Africa: +44 1440 714 850  
 Asia Pacific: +852 3160 9800 | Latin America: 52 (55) 9171-1108  
**For more global phone numbers click here**

© 2022 HID Global Corporation/ASSA ABLOY AB. All rights reserved.  
 2022-01-11-hid-rfid-world-tag-family-ds-en PLT-00286  
 Part of ASSA ABLOY